

02-17-00

A

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : Jonathan C. Kagle et al.

Filed : Herewith

For : METHOD AND APPARATUS FOR
CAPTURING IMAGES

Docket No.: M61.12-0161

jc515 U.S. PTO

09/505223

02/16/00

TRANSMITTAL LETTER

"Express Mail" mailing label number: **EL418980278US**
Date of Deposit: **February 16, 2000**

The following paper(s) and/or fee(s) are being deposited with the United States Postal Service "Express Mail Post Office to Addressee" addressed to BOX PATENT APPLICATION, Assistant Commissioner for Patents, Washington, D.C. 20231:


1. Our checks in the amount of \$816.00 and \$40.00
2. Fee Calculation Sheet (in duplicate)
3. Patent Application comprising the following pages:
 - 1 Abstract
 - 12 Specification
 - 7 Claims
4. 6 Sheets of drawings
5. Executed Declaration and Power of Attorney (3 pages)
6. Executed Assignment and Recordation Form Cover Sheet

Under 37 CFR § 1.136(a)(3), applicant(s) hereby authorize(s) for any future reply, the incorporation of any required petition for extension of time for the appropriate length of time and authorize the charging of fees under § 1.17 to deposit account 23-1123.

Respectfully submitted,

WESTMAN, CHAMPLIN & KELLY, P.A.

By:



Theodore M. Magee, Reg. No. 39,758
Suite 1600 - International Centre
900 Second Avenue South
Minneapolis, Minnesota 55402-3319
Phone: (612) 334-3222
Fax: (612) 334-3312

TMM:ajm

Express Mail No. EL418980278US

PATENT APPLICATION OF
JONATHAN C. KAGLE AND GILAD ODINAK
ENTITLED
METHOD AND APPARATUS FOR CAPTURING IMAGES

Docket No. M61.12-0161

METHOD AND APPARATUS FOR CAPTURING IMAGES

REFERENCE TO RELATED APPLICATIONS

The present application claims priority
5 from a United States Provisional Application having
Serial Number 60/136,517, filed on May 28, 1999 and
entitled "EARLY IMAGE ACQUISITION".

BACKGROUND OF THE INVENTION

The present application relates to digital
10 cameras. In particular, the present invention
relates to image control and processing in digital
cameras.

Digital cameras capture images by
converting light into electrical signals and
15 processing the electrical signals to produce a set of
image data. The image data is then stored in a long-
term memory for later retrieval.

The processing of captured images is
compute-intensive, often making the user wait for the
20 final picture after the shutter button is pressed.
For users who want to take a series of photographs in
rapid succession, this delay is undesirable.

SUMMARY OF THE INVENTION

The present invention provides a method and
25 a camera that perform processing functions based on a
preliminary frame of light before capturing a second
frame of light that forms the final image. After the
light for the final image is captured, additional
post-capture processing is performed on image data

produced from that light. The results of the pre-capture processing are combined with the results of the post-capture processing to produce a final set of image data.

5 In some embodiments, the pre-capture processing includes image processing such as white balance, contrast, and/or red-eye reduction. In other embodiments, the pre-capture processing identifies and modifies performance characteristics
10 of the camera such as available memory, flash parameters and defective pixels in the photo array.

 Under some embodiments, at least one of the pre-capture processing functions is repeated using a portion of the data from the second frame of light.
15 The results based on the second frame of light are compared to the pre-capture results and if the results are too different, the pre-processing function is repeated for the entire second frame of light.

20 Under some embodiments, the pre-capture processing is performed repeatedly until the user depresses a capture button. In other embodiments, the pre-capture processing is performed when the user depresses the capture button half-way, and the post-capture processing is performed when the user
25 depresses the capture button fully. In still other embodiments, the pre-capture processing is performed during a red-eye reduction flash before a main flash is triggered to capture the final image.

30

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a general block diagram of a camera under an embodiment of the present invention.

FIG. 2 is a flow diagram of a method under
5 one embodiment of the present invention.

FIG. 3 is a block diagram of software components under one embodiment of the present invention.

FIG. 4 is a flow diagram of an alternative
10 method under one embodiment of the present invention.

FIG. 5 is a flow diagram of an alternative method under one embodiment of the present invention.

FIG. 6 is a flow diagram of a method of
15 verifying pre-processing results under one embodiment of the present invention.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

FIG. 1 is a block diagram of a camera 200 under an embodiment of the present invention. Light 202 enters camera 200 through a lens assembly 204,
20 which focuses the light onto a photo array 206. In many embodiments, lens assembly 204 is controlled by an auto-focus controller 208 that modifies lens assembly 204 to bring an image into focus on photo array 206.

Photo array 206 is constructed of an array
25 of specialized transistors known as Charge Coupled Devices (CCDs). For black-and-white images, each CCD represents a separate pixel in the captured image. For color images, a set of CCD pixels with overlaid color filters are combined to represent a single pixel, with

each CCD providing information on a different color of light.

Based on the output of the CCDs, photo array 206 transmits an analog signal to an analog-to-digital (A/D) converter 210. A/D converter 210 converts the analog signal into a series of digital values, with each value representing the brightness or intensity of a pixel's color. The digital values produced by A/D converter 210 are stored in a register 212 that receives read and write control signals from an image processor 214. By controlling when A/D converter 210 can write to register 212, image processor 214 is able to capture and store values representing a single frame of light.

Image processor 214 and auto-focus controller 208 are able to access and use the image data in register 212. Auto-focus controller 208 uses the data to adjust lens assembly 204. Image processor 214 uses the image data for a number of processing functions described further below.

In most embodiments, image processor 214 processes the image data in register 212 using software components stored in code storage 216. Intermediate results of this processing are stored in a second register 218, and the final image data resulting from the processing is stored in long-term storage 220.

In most embodiments, image processor 214 receives input from a capture button 222 that is depressed by the user to indicate when the user wants to capture an image. In some embodiments, the user is

able to press capture button 222 half-way down to indicate that they want the camera to prepare to capture an image by, for example, activating the auto-focus feature of the camera.

5 Image processor 214 is also able to set parameters for a flash 224, which is controlled by a flash controller 226. The flash parameters are stored in register 228 by image processor 214 and include parameters such as a red-eye reduction flash parameter,
10 a duration parameter, and a brightness parameter.

 Under the present invention, image processor 214 performs some processing functions before the user indicates that they wish to capture an image. Thus, before capture button 222 is fully depressed, image
15 processor 214 performs one or more functions such as white balance, contrast adjustment, and red-eye reduction. After the user fully depress capture button 222, image processor 214 performs additional post-capture processing functions. The results of the pre-
20 capture and post-capture processing functions are then combined to produce a final set of image data. By performing some of the image processing functions before the user tries to capture an image, the present invention reduces the post-capture processing time.

25 FIG. 2 is a flow diagram of a method for capturing images under one embodiment of the present invention. Under one embodiment, the process of FIG. 2 is performed by image processor 214 by invoking a set of software components. FIG. 3 provides a block
30 diagram of some of these components, which are

described below in connection with the method of FIG. 2.

The method of FIG. 2 begins at step 300 and proceeds to step 302 where a system control component 400 invoked by image processor 214 causes image data for a frame of light to be written to register 212. System control 400 then retrieves the stored values from register 212 and at step 304 invokes a pre-capture process control 402 that controls one or more pre-capture processing functions.

Under one embodiment, pre-capture process control 402 invokes one or more separate image processing components such as white balance component 404, red-eye reduction component 406, contrast adjustment component 408, flesh tone correction component 410, and edge enhancement component 412 of FIG. 3. When invoked, each of these components is given access to the image data. When a component completes its operation, it typically returns one or more processing values to pre-capture process control 402. Under some embodiments, pre-capture process control 402 invokes two or more of the image processing components in parallel. In other embodiments, the image processing components are invoked serially.

In some embodiments, pre-capture process control 402 also invokes processing functions to test the performance of some hardware components of the camera. For example, under one embodiment, pre-capture process control 402 invokes a defective pixel detection component 428, which determines if one or more of the

CCD transistors is malfunctioning. In other embodiments, pre-capture process control 402 invokes a memory availability component 430, which determines if long term image storage 220 of FIG. 1 has enough
5 available memory to accommodate the next image. If there is insufficient available memory, system control 400 either sends a message to the user through a display driver 423 in operating system 416 or reallocates the memory resources by remapping virtual
10 address space, terminating other components or minimizing other components. When system control 400 reallocates the memory resources, it acts as a memory management component. As shown in FIG. 1, this message is provided to the user through a display 230 that is
15 controlled by a display interface 232. Display interface 232 receives its display data from display driver 423 in image processor 214.

Returning to the method of FIG. 2, after step 304, system control 400 checks to see if the user
20 has pressed the image capture button at step 306. Under some embodiments, information as to whether the user has pressed the button is provided by a user input component 414 shown in operating system 416 in FIG. 3. If the capture button has not been pressed at step 306,
25 the process of FIG. 2 returns to step 302, and steps 302 and 304 are repeated.

If the capture button has been pressed at step 306, system control component 400 captures image data for a second frame of light at step 308. System
30 control component 400 then invokes a post-capture

process control component 418 that invokes one or more image processing components at step 310. Some of the image processing components, such as compression component 420 of FIG. 3, change the image data as they
5 process it. If another image processing component is invoked after a component that changes the image data, the subsequent image processing component receives the modified image data. Post-capture process control 418 also acts as an image production control that utilizes
10 the results of the pre-capture processing components and the post-capture processing components to produce a final set of image data.

At step 312, the final set of image data is stored in long-term image storage 220 of FIG. 1. Under
15 the embodiment of FIG. 3, the process of storing the final image data is controlled by operating system 416. After the final image data has been stored, the process of FIG. 2 ends at step 314.

FIG. 4 provides a flow diagram for an
20 alternative method of capturing images under the present invention. The process of FIG. 4 starts at step 480 and continues at step 482 where system control 400 waits for the user to depress the capture button. When the user depresses the capture button, system
25 control 400 uses a flash control component 422 in operating system 416 of FIG. 3 to trigger a red-eye reduction flash at step 484 of FIG. 4. At step 486, system control 400 captures image data generated from a frame of light that includes light from the red-eye
30 reduction flash. The red-eye reduction flash

illuminates the subject of the photograph so that the captured image has color, contrast, and brightness characteristics more similar to the image produced when the main flash is later triggered, as described below.

5 At step 488, system control 400 invokes pre-capture process control 402, which invokes one or more processing components as described above.

10 In addition to using some or all of the processing components described above, some embodiments that utilize the method of FIG. 4 perform an additional pre-capture processing function. This additional function is performed by flash control 424 in FIG. 3 and involves adjusting the parameters of the camera's flash system. For example, in some embodiments, flash
15 control 424 changes the duration and/or brightness of the flash. The changes to the flash parameters are stored in register 228 of FIG. 1 through flash control 422 of operating system 416.

20 When the pre-capture processing is complete, the method of FIG. 4 continues at step 490 where system control 400 triggers the main flash. The image generated by the light of the main flash is then captured at step 492. At step 494, system control 400 invokes post-capture process control 418, which invokes
25 one or more post-capture processing functions as described above. Post-capture process control 418 utilizes the results of the pre-capture processing and post-capture processing to form a final set of image data that is stored before the process of FIG. 4 ends
30 at step 496.

FIG. 5 provides a flow diagram of an alternative method for capturing images under the present invention. The method of FIG. 5 begins at step 520 and proceeds to step 522 where system control 400
5 waits to receive a pre-capture event. The pre-capture event can be generated by a software routine based on a timer or some other triggering event or can be generated when the user presses the capture button half-way down. When the pre-capture event occurs, the
10 method of FIG. 5 continues at step 524 where system control 400 captures image data for a first frame of light. At step 526, system control 400 invokes pre-capture process control 402, which invokes one or more pre-capture processing components as described above in
15 connection with FIGS. 2 and 3. In the method of FIG. 5, the pre-capture processing components can include an auto-focus component such as auto-focus component 426 of FIG. 3.

After pre-capture process control 402 has
20 finished executing, system control 400 waits for the user to fully depress the capture button at step 528. When the user fully depresses the capture button, system control 400 retrieves a new set of image data based on a second frame of light that entered the
25 camera just after the capture button was depressed. This is shown in step 530 of FIG. 5. System control 400 then invokes post-capture process control 418 at step 532. Post-capture process control 418 invokes one or more post-capture processing components and utilizes
30 the results from the pre-capture processing components

and the post-capture processing components to form a set of final image data. System control 400 then stores the final image data before the method of FIG. 5 ends at step 534.

5 Under some embodiments of the invention, post-capture process control 418 invokes a verify pre-capture results component 432 to verify the results from one or more of the pre-capture components before utilizing those results. Such verification is helpful
10 because the lighting conditions may have changed between the time when the image data for the first frame of light was collected and the time when the image data for the second frame of light was collected. FIG. 6 is a flow diagram of one method for verifying
15 the pre-capture processing results.

The method of FIG. 6 begins at step 600 where a portion of the image data for the second frame of light is selected. At step 602, this sub-set of image data is provided to the pre-capture processing
20 component that is having its results verified. This produces a verification result that is compared to the original result produced by the pre-capture processing component for the first frame of light. This comparison is performed in step 604. The difference
25 between the two results is compared to a threshold at step 606. If the two results differ by more than the threshold, all of the image data for the second frame of light is passed to the pre-capture processing component to generate a new result at step 608. If the
30 two results differ by less than the threshold, the

original result formed from the first frame of light is used at step 610. Thus, if image conditions have changed substantially between the first and second frames of light, the pre-capture processing functions are repeated using the second frame of light instead of the first frame of light. However, if image conditions have not changed substantially between the frames of light, the results formed from the first frame of light are used to determine the final image data.

10 Although the present invention has been described with reference to particular embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention.

WHAT IS CLAIMED IS:

1. A method of capturing images in a camera, the method comprising:

acquiring a first set of image data based on a first frame of light entering the camera;

performing at least one pre-capture processing function on the first set of image data to produce a pre-capture result;

acquiring a second set of image data based on a second frame of light entering the camera;

performing at least one post-capture processing function on the second set of image data to produce a post-capture result;

generating final image data based on the pre-capture result and the post-capture result.

2. The method of claim 1 wherein performing at least one pre-capture processing function comprising performing a white balance processing function to produce a white balance value as the pre-capture result.

3. The method of claim 1 wherein performing at least one pre-capture processing function comprises

performing a contrast adjustment function to produce a contrast value as the pre-capture result.

4. The method of claim 1 wherein performing at least one pre-capture processing function comprises performing a red-eye reduction function to produce a set of red-eye compensation values as the pre-capture result.

5. The method of claim 1 wherein performing at least one pre-capture processing function comprises performing a flesh tone correction function to produce a flesh tone correction value as the pre-capture result.

6. The method of claim 1 wherein performing the at least one pre-capture processing function further comprises determining the amount of available memory for storing the final image data and if the available memory is less than the amount of memory needed to store the final image data, indicating to the user that there is insufficient memory before acquiring the second set of image data.

7. The method of claim 1 wherein performing the at least one pre-capture processing function further comprises determining the amount of available memory for storing the final image data and if the available memory is less than the amount of memory

needed to store the final image data, reallocating memory before acquiring the second set of image data.

8. The method of claim 1 further comprising receiving an external indication that an image should be captured before acquiring the second set of image data.

9. The method of claim 1 further comprising receiving a pre-capture event before acquiring the first set of image data.

10. The method of claim 9 wherein the pre-capture event is an indication that a user has pressed a capture button half-way down.

11. The method of claim 9 wherein the pre-capture event is produced by a software routine.

12. The method of claim 1 further comprising triggering a red-eye reduction flash before acquiring the first set of image data and triggering a main flash before acquiring the second set of image data.

13. The method of claim 12 wherein performing the at least one pre-capture processing function comprises determining if a set of flash parameters is properly set based on the red-eye reduction flash and producing a new set of flash parameters as the pre-capture result if the flash parameters are not

properly set and wherein generating the final image data based on the pre-capture result and the post-capture result comprises using the new set of flash parameters when the main flash is triggered and generating the final image data based on the corresponding post-capture result.

14. The method of claim 1 further comprising performing at least one pre-capture processing function on a portion of the second set of image data to produce a test result and comparing the test result to a pre-capture result.

15. The method of claim 14 further comprising performing the pre-capture processing function on the entire second set of image data if the test result and pre-capture result are not sufficiently similar.

16. The method of claim 1 wherein performing at least one pre-capture processing function comprises identifying defective pixels in the camera and providing the identity of the defective pixels as the pre-capture result.

17. A camera having processor-executable components for capturing images, the components comprising:

- an image acquisition component capable of acquiring image data representing a single frame of light;

a pre-capture processing component capable of performing a pre-capture function based on image data acquired by the image acquisition component for a first frame of light;

a post-capture processing component capable of performing a post-capture function on image data acquired by the image acquisition component for a second frame of light; and

an image production component capable of producing final image data based on results from the pre-capture function and the post-capture function.

18. The camera of claim 17 wherein the pre-capture processing component is capable of performing a white balance function based on the image data for the first frame of light.

19. The camera of claim 17 wherein the pre-capture processing component is capable of performing a contrast function based on the image data for the first frame of light.

20. The camera of claim 17 wherein the pre-capture processing component is capable of performing a red-eye reduction function based on the image data for the first frame of light.

21. The camera of claim 17 wherein the pre-capture processing component is capable of performing a memory resource function to determine if there is sufficient available memory to store the final image data.

22. The camera of claim 21 further comprising a user notification component capable of notifying the user when there is insufficient memory to store the final data before the image acquisition component acquires image data for a second frame of light.

23. The camera of claim 18 further comprising a memory management component that is capable of reallocating memory resources before the image acquisition component acquires image data for a second frame of light.

24. The camera of claim 17 wherein the pre-processing component performs a pre-capture function on a portion of the image data for the second frame of light and wherein the camera further comprises a comparison component capable of comparing the results of performing the same pre-capture function on the image data for the first frame of light and on the portion of the image data for the second frame of light.

25. The camera of claim 24 wherein the comparison component causes the pre-capture

processing component to perform the pre-capture function on all of the image data for the second frame of light when the results of performing the pre-capture function on a portion of the image data for the second frame of light are substantially different than the results of performing the pre-capture function on the image data for the first frame of light.

26. The camera of claim 17 wherein the pre-capture processing component is capable of adjusting flash parameters of the camera based on image data acquired for the first frame of light.

27. The camera of claim 17 wherein the pre-capture processing component is capable of identifying defective pixels in the camera based on image data acquired for the first frame of light.

METHOD AND APPARATUS FOR CAPTURING IMAGES

ABSTRACT OF THE DISCLOSURE

A method and a camera perform processing functions based on a preliminary frame of light before capturing a second frame of light that forms a final camera image. After the light for the final image is captured, additional post-capture processing is performed on image data produced from that light. The results of the pre-capture processing are combined with the results of the post-capture processing to produce a final set of image data.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

COMBINED DECLARATION AND
POWER OF ATTORNEY
IN ORIGINAL APPLICATION

Attorney Docket No.

M61.12-0161

SPECIFICATION AND INVENTORSHIP IDENTIFICATION

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and joint inventor of the subject matter which is claimed, and for which a patent is sought, on the invention entitled METHOD AND APPARATUS FOR CAPTURING IMAGES the specification of which,

(check one) ☒ is attached hereto.

☐ was filed on _____ as Appln. Serial No. _____.

☐ and was amended on _____.

☐ was described and claimed in PCT International Application No. _____ filed on _____ and as amended under PCT Article 19 on _____.

ACKNOWLEDGEMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR

I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is known to me to be material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56.

PRIORITY CLAIM (35 USC § 119)

I claim foreign priority benefits under Title 35, United States Code, § 119(a-d) of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Number	Country	Day/Month/Year Filed	Priority Claimed
_____	_____	_____	Yes____ No____
_____	_____	_____	Yes____ No____

Prior Provisional Application(s)

I hereby claim the benefit under Title 35, United States Code §119(e) of any United States Provisional Application(s) listed below:

Number	Day/Month/Year Filed
<u>60/136,517</u>	<u>May 28, 1999</u>
_____	_____

PRIORITY CLAIM (35 USC § 120)

I claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below. Insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35 United States Code § 112, I acknowledge the duty to disclose to the Patent Office all information known to me to be material to patentability as defined in Title 37 Code of Federal Regulations § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Appln. Ser. No.	U.S. Serial No. (if any under PCT)	Filing Date	Status
_____	_____	_____	_____
_____	_____	_____	_____

DECLARATION

I declare that all statements made herein that are of my own knowledge are true and that all statements that are made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

POWER OF ATTORNEY


I appoint the following attorneys and agents to prosecute the patent application identified above and to transact all business in the Patent and Trademark Office connected therewith, including full power of association, substitution and revocation: Judson K. Champlin, Reg. No. 34,797; Joseph R. Kelly, Reg. No. 34,847; Nickolas E. Westman, Reg. No. 20,147; Steven M. Koehler, Reg. No. 36,188; David D. Brush, Reg. No. 34,557; John D. Veldhuis-Kroeze, Reg. No. 38,354; Deirdre Megley Kvale, Reg. No. 35,612; Theodore M. Magee, Reg. No. 39,758; Peter S. Dardi, Reg. No. 39,650; Christopher R. Christenson, Reg. No. 42,413; John A. Wiberg, Reg. No. 44,401; Brian D. Kaul, Reg. No. 41,885; Katie E. Sako, Reg. No. 32,628; and Daniel D. Crouse, Reg. No. 32,022.

I ratify all prior actions taken by Westman, Champlin & Kelly, P.A. or the attorneys and agents mentioned above in connection with the prosecution of the above-mentioned patent application.

DESIGNATION OF CORRESPONDENCE ADDRESS

Please address all correspondence and telephone calls to Theodore M. Magee in care of:

WESTMAN, CHAMPLIN & KELLY, P.A.
Suite 1600 - International Centre
900 Second Avenue South
Minneapolis, Minnesota 55402-3319
Phone: (612) 334-3222 Fax: (612) 334-3312

Inventor: 
(Signature)

Date: 2/5/2000

Inventor: Jonathan C. Kagle
(Printed Name)

Residence: Redmond, Washington Citizenship: U.S.A.

P.O. Address: 14324 NE 84th Ct., Redmond, WA 98052

(Signatures Continued on Next Page)

Date: 2/15/2000

Citizenship: U.S.A.

Residence: Bellevue, Washington

P.O. Address: 12342 NE 26th Pl., Bellevue, WA 98005